

Dati attuali al giorno: 03-06-2026 22:40

Link al prodotto : <https://www.cnc-world.it/inchiostro-dtf-1000ml-y2-ciano-p-786.html>

Inchiostro DTF 1000ml Y2 - Ciano



Prezzo lordo	49.00 EUR
Prezzo netto	40.16 EUR
disponibilità	Disponibile
Tempo di spedizione	48 ore
Numero dell articolo	004INK-DTF
codice del produttore	Y2
Produttore	CNCTech

Descrizione del prodotto

Inchiostro DTF 1000ml Y2 - Cyan/Ciano



CNCWORLD

Y2 DTF Ink 1000ml

Type: Hard Ink

Lot no.: 2503P0246

Compatible printheads:

DX5 | DX7 | TX800 | XP600 | i3200 | I1600 | 4720 | 1390

CAUTIONS:

Warning: For industrial use. Causes skin and eye irritation. May cause an allergic reaction.

Personal Protective Equipment (PPE)

• Wear eye protection, gloves and a dust mask. Do not touch your face and avoid contact with your eyes and clothing.

Use handling:

• Store in a well-ventilated area. Avoid inhaling vapors.

• Do not ingest. If you get it on your skin, wash it off immediately with soap and water.

• Do not get it in the eyes and hair.

• Do not use in confined spaces. Ventilate well during use. Do not use in areas with high humidity. Do not use in areas with high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

• Do not use in areas with high humidity and high temperature.

Inchiostro di alta qualità per stampanti DTF della gamma CMYK con capacità di 1000 ml, garantisce una resa cromatica ideale, un'elevata adesione e durabilità sui materiali.

Tipo: Inchiostro rigido

Colore: Ciano

Data di scadenza: almeno 6 mesi

Testine di stampa compatibili: DX5 | DX7 | DX8 | TX800 | XP600 | I3200 | I1600 | 4720 | 1390