

Dati attuali al giorno: 03-06-2026 21:50

Link al prodotto : <https://www.cnc-world.it/primer-acrilico-dz-per-stampanti-uv-p-798.html>



Primer acrilico DZ per stampanti UV

Prezzo lordo	129.00 EUR
Prezzo netto	105.74 EUR
Prezzo precedente	169.00 EUR
disponibilità	Disponibile
Tempo di spedizione	48 ore
Numero dell'articolo	009INK
codice del produttore	X1
Produttore	CNCTech

Descrizione del prodotto

Primer DZ per acrilico per stampanti UV



CNCWORLD

**UV Primer DZ Pre-coating liquid
for Acrylic 1000ml**

Lot no.: 2508T0441

Compatible printheads:

DX5 | DX7 | TX800 | XP600 | I3200 | I1600 | 4720 | 1390

CAUTIONS:

Warning! For industrial use. Causes skin and eye irritation. May cause an allergic skin reaction.
Personal Protective Equipment (PPE):
1. Always wear safety glasses or a face shield. Direct contact can cause serious and permanent eye damage.
2. Always use chemical-resistant protective gloves (e.g., nitrile, PU) as a strong precaution.
Safe handling:
1. Work in a well-ventilated area, avoid inhaling vapors.
2. Do NOT touch the skin with bare skin. In case of contact, immediately wash skin with soap and water.
3. Keep away from fire and heat sources.
First Aid:
1. Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention.
2. Skin Contact: Remove contaminated clothing and wash skin with soap and water.
3. Inhalation: Move the affected person to fresh air.
Storage and disposal:
1. Store in a tightly sealed container in a cool, dark, and dry place, away from sunlight.
2. Dispose of the end-user containers in accordance with local chemical waste regulations.



Il primer per acrilico (UV Primer) è un agente chimico specializzato che funge da **ponte adesivo** tra la superficie del materiale e l'inchiostro UV. È un elemento chiave nel processo di stampa UV su supporti difficili.

Rinforza l'adesione dell'inchiostro alle superfici sintetiche, aumentando **elasticità e resistenza** ai graffi, fondamentale nella produzione di gadget e targhe.

Data di scadenza: almeno 6 mesi

Testine di stampa compatibili: DX5 | DX7 | DX8 | TX800 | XP600 | I3200 | I1600 | 4720 | 1390